

CHULA VISTA FIRE DEPARTMENT

FIRE PREVENTION DIVISION

FIRE LANE IDENTIFICATION

Fire Lanes shall be identified in accordance with one of the details below:

Detail A - No Stopping Sign



Notes:

- Signs shall be in accordance with Caltrans/FHWA standard [R26F] (See page 2)
- The face of the sign shall be parallel to the roadway
- Spaced at maximum intervals of 50ft on center or fraction thereof
- Signs shall be mounted on posts 7ft above grade or on building as approved
- Signs shall be .080 gauge aluminum
- Signs shall have ASTM Type IV High Intensity reflective sheeting
- Signs shall be provided with a protective overlay film

Detail B - Curb Painting - Both sides of fire lane unless otherwise approved



Notes:

- Entire curb shall be painted red [two coats]
- White lettering "NO STOPPING FIRE LANE" [two coats]
- Lettering height minimum of 4 inches
- Lettering to be on top of designated curbing
- Spaced at maximum intervals of 25ft on center or fraction thereof
- Paint shall be suitable for exterior application and fade resistant

$Detail\ C\ -\ Striping\ (with\ no\ curb)\ \ -\ \textbf{Both\ sides\ of\ fire\ lane\ unless\ otherwise\ approved}$

NO STOPPING - FIRE LANE

Notes:

- Minimum width of this red stripe shall be 8 inches [two coats]
- White lettering "NO STOPPING FIRE LANE" [two coats]
- Lettering height minimum of 6 inches
- Spaced at maximum intervals of 25ft on center or fraction thereof
- Paint shall be suitable for exterior application and fade resistant

CHULA VISTA FIRE DEPARTMENT

FIRE PREVENTION DIVISION

NO STOPPING SIGN Signs shall be in accordance with Caltrans/FHWA standard [R26F]



SIGN	DIMENSIONS (INCHES)											
	A	В	C	D	E	F	G	Н	J	Ķ	L	• м
STANDARD	12	18	1/4	5 1/2	1 1/2	3 1/2B	7/8	3B	2 1/48	1/2C	5/8	5 5/8
SPECIAL	24	30	1/2	11	2 1/2	6B	1 1/2	5B	3 1/2B	3/4C	1 1/4	10

COLORS

LEGEND & BORDER - RED

BACKGROUND - WHITE (REFL.)

THE POLICY FOR INTENDED USAGE OF THIS SIGN IS SHOWN ON REVERSE SIDE.